

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A built-in lamp comprising a holder for fastening in an installation surface (11), ~~in particular in a room ceiling~~, a bulb (6) and a reflector, with a reflector opening disposed in the direction of illumination defining a direct light discharge region (1), which is surrounded by a diffuse light discharge region (2) such that scattered light is discharged from the diffuse light discharge region (2) around the direct light discharge region (1), characterized in that

the bulb (6) and the direct light reflector (4) are arranged in a housing (10) whose inner surface is made at least regionally as an additional reflector (7); and

in that the housing (10) is terminated in at least a largely dust-proof manner by a translucent scattering plate (13, 15) in the region of the diffuse light discharge region (2) and by a plate (13, 14) which is in particular transparent in the region of the direct light discharge region (1), and

wherein the direct light discharge region (1) has a circular shape, and the diffuse light discharge region (2) is bounded on the inner side by a circular line (3) and on the outer side by a polygonal line or by a further circular line.

2. (original) A built-in lamp in accordance with claim 1, characterized in that the direct light discharge region (1) and the diffuse light discharge region (2) can be acted on by a common bulb (6).

3. (currently amended) A built-in lamp in accordance with claim 1 ~~or claim 2~~, characterized in that the reflector opening defining the direct light discharge region (1) is associated with a direct light reflector (4) on whose side remote from the direct light discharge region (1) an additional reflector or background reflector (7) is provided.

4. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that a light passage region is formed between the additional reflector (7) and the direct light reflector (4).
5. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the diffuse light discharge region (2) can only be acted on indirectly by the bulb (6) via the additional reflector (7).
6. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the additional reflector (7) is formed at least partly by at least one planar or pre-determinably curved or kinked reflector surface which ensures a pre-determinable splitting of the portion of the reflected light directed to the direct light discharge region (1) and to the diffuse light discharge region (2).
7. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the housing (10) is made to be light-proof and/or dust-proof.
8. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the additional reflector (7) is made to be specularly reflecting or diffusely reflecting.
9. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the direct light reflector (4) is made to be specularly reflecting on its inner side.
10. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the direct light reflector (4) is made to be specularly reflecting or diffusely reflecting on its outer side.
11. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the bulb (6) is located inside the direct light reflector (4) and/or between the direct light reflector (4) and the additional reflector (7).

12. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the translucent scattering plate (13) and the plate (13), which is in particular transparent, are made in one piece.

13. (canceled)

14. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the ~~diffuse light discharge region (2) is bounded on the inner side by a circular line (3) and on the outer side by a polygonal line, in particular by is a rectangular or square line (8), or by a further circular line~~ polygonal line is a rectangular or square line (8).

15. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the direct light reflector (4) is held pivotably in the housing (10).

16. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that a common inclination of the direct light discharge region (1) with the diffuse light discharge region (2) is adjustable with respect to the installation surface (11) by a pivoting of the direct light reflector (4); or

in that an inclination of the direct light discharge region (1) is adjustable with respect to the diffuse light discharge region (2) by a pivoting of the direct light reflector (4).

17. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the direct light reflector (4) is held pivotably in the housing (10) together with the bulb (6).

18. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the direct light reflector (4) is held pivotably in the housing (10).

19. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that a common inclination of the direct light discharge region (1) with the diffuse light discharge region (2) is adjustable with respect to the installation surface

(11) by a pivoting of the direct light reflector (4); or in that an inclination of the direct light discharge region (1) is adjustable with respect to the diffuse light discharge region (2) by a pivoting of the direct light reflector (4).

20. (currently amended) A built-in lamp in accordance with ~~any one of the preceding~~ claim[[s]] 1, characterized in that the direct light reflector (4) is held pivotably in the housing (10) together with the bulb (6).